

cl  
Cume  
pg 1

an insulating film on a first substrate;  
a first electrode having a plurality of slit patterns directly contacting the insulating film;  
at least one light-shielding layer below each slit pattern;  
a second electrode on a second substrate; and  
a liquid crystal layer between the first and second substrates, the liquid crystal layer having different alignment directions by each slit pattern.

---

Sub  
cl  
pg 2

4. (Twice Amended) A liquid crystal display device comprising:  
an insulating film on a first substrate;  
a first electrode having a plurality of slit patterns directly contacting the insulating film;  
at least one light-shielding layer below the first electrode and the slit patterns;  
a second electrode on a second substrate; and  
a liquid crystal layer between the first and second substrates, the liquid crystal layer having different alignment directions by each slit pattern.

---

pg 3  
Sub  
cl

8. (Twice Amended) A method of fabricating a liquid crystal display device on first and second substrates, comprising:  
forming at least one light-shielding layer on the first substrate;  
forming an insulating layer on the entire surface of the first substrate and on the at least one light-shielding layer;  
forming a first electrode directly on the insulating layer, the first electrode having a plurality of slit patterns over the light-shielding layer;  
forming a second electrode on the second substrate;

c1  
Cmt  
p3  
assembling the first and second substrates; and

forming a liquid crystal layer having different alignment directions by each slit pattern  
between the first and second substrates.

---